

# Standard Pattern



**Standard Pattern** Dark Grey

## Fittings and accessories

**Ridges:** - Half round  
- Segmental

**Mono ridges:** - Half round

**Hips:** - Half round  
- Segmental

**Valleys:** - Lead  
- Fibreglass

**Clips:** - Tile, Eaves, Verge

## Roofing systems

**Dry roof systems:** - Ridge, Hip

**Ventilation systems:** - Ridge  
- Eaves  
- Top abutment  
- Tile vent\*  
- Gas terminals

\* Concealed tile vent min. pitch 22.5°

Easy to install and highly durable, this tile is ideal for re-roofing and comes in convenient banded packs of eight.

**Tile fixing:** Download zonal fixing table from [www.sandtoft.com](http://www.sandtoft.com). Alternatively, use our Fixing SPEC service by completing your details online or calling 0844 9395 999.

## Technical data


Minimum roof pitch	17.5° Smoothfaced 30° Sandfaced
Headlap (minimum)	75 mm
Headlap (maximum)	120 mm
Batten spacing at max. gauge	305 mm
Batten spacing at min. gauge	260 mm
Size of tile	380 x 230 mm
Covering capacity at max. gauge	16.5 tiles per m <sup>2</sup>
Cover width	200 mm
Profile depth	40 mm
Hanging length	355 mm
Weight as laid	49.5 kg per m <sup>2</sup>
Weight per 1000	3.0 tonnes
Weight per tile	3.0 kg
Weight per pallet (inc. pallet)	1.1 tonnes
Quantity per pallet	360
Battens per m <sup>2</sup>	3.30 m
Batten size	
Up to 450 mm rafter centres	38 x 25 mm
Up to 600 mm rafter centres	50 x 25 mm
Nail size/type for tiles	50 x 3.35 mm aluminium clout head
Nail size/type for tile clips	50 x 3.35 mm aluminium clout head
BRE Green Guide rating	A+

Note: Unless otherwise stated, data is based on tiles laid at minimum headlap.

## Colours Sandfaced



## Smoothfaced



**Enquiries:** Contact Customer Support on 0844 9395 900 or visit our website at [www.sandtoft.com](http://www.sandtoft.com)

