

Shire Pantile



Shire Rustic

Fittings and accessories

Tile fittings: - LH verge tile

- Dentil slips

Ridges: - Half round

- Segmental

Mono ridges: - Half round

Hips: - Half round

- Segmental

Eaves: - Bird comb filler

Valleys: - Lead

- Fibreglass

Clips: - Tile, Eaves, Verge

See pages 26-29.

Roofing systems

Dry roof systems: - Ridge, Hip

Ventilation systems: - Ridge

- Eaves

- Top abutment

- Tile vent

- Gas terminals

See pages 108-123.

All the proportions of a classic pantile profile available in seven distinctive colours.

Technical data


Minimum roof pitch	22.5° Smoothfaced 30° Sandfaced
Headlap (minimum)	75 mm
Headlap (maximum)	120 mm
Batten spacing at max. gauge	305 mm
Batten spacing at min. gauge	260 mm
Size of tile	380 x 230 mm
Covering capacity at max. gauge	16.5 tiles per m ²
Cover width	200 mm
Profile depth	70 mm
Hanging length	360 mm
Weight as laid	47.9 kg per m ²
Weight per 1000	2.9 tonnes
Weight per tile	2.9 kg
Weight per pallet (inc. pallet)	1.1 tonnes
Quantity per pallet	360
Battens per m ²	3.30 m
Batten size	
Up to 450 mm rafter centres	38 x 25 mm
Up to 600 mm rafter centres	50 x 25 mm
Nail size/type for tiles	38 x 3.35 mm aluminium clout head
Nail size/type for tile clips	50 x 3.35 mm aluminium clout head
BRE Green Guide rating	A+

Note: Unless otherwise stated, data is based on tiles laid at minimum headlap.


Tile fixing: Download zonal fixing table from www.sandtoft.com. Alternatively, use our Fixing SPEC service by completing your details online or calling 0844 9395 999.

Colours

Sandfaced



02 Antique No. 2




03 Mottled Red


Smoothfaced




10 Brown



11 Terracotta Red



12 Rustic



14 Dark Grey



18 Charcoal